

Tarred adhesive strap

- cod. 11128007



TECHNICAL SPECIFICATIONS:

- Specific weight (ASTM D792): 1,20 +/- 0,10;
- Needle penetration (ASTM D5): 50/60 x 0.1 mm, 50 g/5s
- Adhesion (ASTM D1344): > 150 KPa;
- Elongation (ASTM D1344): > 100%;
- K value: 0.29 W/mK;
- Operating temperature: from -40°C to 100°C
- Length 10 m - Thickness 5 mm - Width 50 mm
- Ideal for preventing condensation on pipes
- The product does not require the use of adhesives

USE:

The surfaces must be clean, dry and free from dirt, grease, oil or water.

Cut the desired length from the roll and remove the release paper while wrapping the tape in a spiral around the pipe or connection. Tighten the coil and press the edges together.

Avoid elongating the coil.

DIMENSIONS

CODE	LENGTH [m]	WIDTH [mm]	THICKNESS [mm]
11128007	10	50	5

ITEMS

CODE	DESCRIPTION
11128007	BITUMIZED-ADHESIVE TAPE 3x50 mm

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.