

RHTS

1 HP recovery and recycling station with oil separator for R32 gas

- cod. TSC100021



TECHNICAL SPECIFICATIONS:

- Voltage: 220 - 204 V 50 Hz
- 1 HP oil-free compressor
- Maximum current 4A
- Frequency 50 Hz
- High pressure shut-down 38.5 bar
- Refrigerants: R12, R134A, R401C, R406A, R500, TR422ABCD (R22), R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509, R402A, R404A, R407A, R410A, R507, R32, HFO-1234YF
- Recovery rates of TR422ABCD (R22): vapour: 0.25 kg/min; fluid: 1.80 kg/min; push-pull: 5.60 kg/min
- Final vacuum 15" Hg
- Operating temperature from 0°C to +40°C
- Outer body made of high-impact blow-moulded polyethylene
- Dimensions W 450 x H 355 x D 250 mm
- Net weight 14.7 kg
- F-GAS certifiable

ITEMS

CODE	DESCRIPTION
TSC100021	"RHTS" RECOVERY & RECYCLING STATION WITH OIL SEPARATOR FOR R32

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.