

Gas flexible hose for kitchen connection covered in transparent sheath F / F

- cod. 25000000 - cod. 25000010 - cod. 25000020
- cod. 25000030 - cod. 25000040 - cod. 25000050



TECHNICAL SPECIFICATIONS:

- Twist in stainless steel AISI 304 EN 10088 - 1din 1.4301
- AISI 316L EN 10088 - 1 DIN 1.4404 stainless steel pipe
- 1/2" couplings stainless steel AISI 303 EN 10088 - 1 DIN 1.4301
- Outer yellow PVC coating - transparent self-extinguishing
- Max pressure 0.5 bar
- Max temperature +100 °C
- Available in 500 - 750 - 1000 - 1250 - 2000 mm
- Flexible pipe with gaskets and sealing caps

ITEMS

CODE	DESCRIPTION
25000000	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 500MM
25000010	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 750MM
25000020	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 1000MM
25000030	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 1250MM
25000040	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 1500MM
25000050	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 2000MM

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.