

DATASHEET

rev. 00 - 28/11/2022



Water pressure gauge ø 50 with red hand

20000010 - 20000020 - 20000030
20000040 - 20000050 - 20000060
20000070 - 20000080



TECHNICAL SPECIFICATIONS:

- ABS case and dial
- Plastic glass (Lustran)
- Class 1.6
- Includes red needle
- Copper alloy spring
- Operating temperature -20°C to +80°C
- Reference standard UNI EN 2004/22/EC
- Scale available in 4 - 6 - 10 - 16 bar

TECHNICAL DATA

CODE	LADDER [bar]	COUPLER
20000010	0-4	1/4"
20000020	0-6	1/4"
20000030	0-10	1/4"
20000040	0-16	1/4"
20000050	0-4	1/4"
20000060	0-6	1/4"
20000070	0-10	1/4"
20000080	0-16	1/4"

ITEMS

CODE	DESCRIPTION
20000010	PRESSURE GAUGE Ø 50 WITH RADIAL CONNECTION, SCALE 0-4, 1/4"
20000020	PRESSURE GAUGE Ø 50 WITH RADIAL CONNECTION, SCALE 0-6, 1/4"
20000030	PRESSURE GAUGE Ø 50 WITH RADIAL CONNECTION, SCALE 0-10, 1/4"
20000040	PRESSURE GAUGE Ø 50 WITH RADIAL CONNECTION, SCALE 0-16, 1/4"
20000050	PRESSURE GAUGE Ø 50 WITH REAL CONNECTION, SCALE 0-4, 1/4"
20000060	PRESSURE GAUGE Ø 50 WITH REAL CONNECTION, SCALE 0-6, 1/4"
20000070	PRESSURE GAUGE Ø 50 WITH REAL CONNECTION, SCALE 0-10, 1/4"
20000080	PRESSURE GAUGE Ø 50 WITH REAL CONNECTION, SCALE 0-16, 1/4"