

# DATASHEET

rev. 00 - 28/11/2022



Gas flexible hose for kitchen connection  
covered in transparent sheath M / F

25000060 - 25000070 - 25000080  
25000090 - 25000100 - 25000110



## TECHNICAL SPECIFICATIONS:

- Twist in stainless steel AISI 304 EN 10088 - 1DIN 1.4301
- AISI 316L EN 10088 - 1 DIN 1.4404 stainless steel pipe
- 1/2" couplings stainless steel AISI 303 EN 10088 - 1 DIN 1.4301
- Outer yellow PVC coating - transparent self-extinguishing
- Max pressure 0.5 bar
- Max temperature +100°C
- Available in 500 - 750 - 1000 - 1250 - 2000 mm
- Flexible pipe with gaskets and sealing caps

## ITEMS

CODE	DESCRIPTION
25000060	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 500MM
25000070	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 750MM
25000080	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 1000MM
25000090	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 1250MM
25000100	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 1500MM
25000110	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 2000MM