

# GREY LINE

single insulated copper pipe 20 m

- cod. SCD600015 - cod. SCD600016 - cod. SCD600017  
- cod. SCD600018 - cod. SCD600019



## DESCRIPTION

Copper pipe Cu-DHP (in accordance with EN 12735-1) covered with a closed-cell polyethylene foam sheath with a robust grey tear-resistant outer film.

DOES NOT CONTAIN FREON (HCFCs, CFCs or HFCs) in accordance with Law No. 549 of 28/12/1993.

## TECHNICAL DATA

CODE	Ø [inch]	Ø [mm]	COPPER THICKNESS [mm]	SHEATH THICKNESS [mm]	MAX. OPERATING PRESSURE [bar]	BURST PRESSURE [bar]
SCD600015	CU 1/4"	6.35	0.8	6	107.9	515.9
SCD600016	CU 3/8"	9.52	0.8	6	71	339.4
SCD600017	CU 1/2"	12.7	0.8	6	53.9	258
SCD600018	CU 5/8"	15.88	1	10	50.8	243.1
SCD600019	CU 3/4"	19.05	1	10	42.4	202.6

## TECHNICAL SPECIFICATIONS OF THE SHEATH

SPECIFICATIONS	TECHNICAL DATA
Operating temperature	-45° C +105° C
Density	30 kg / m <sup>3</sup>
Technical conductivity coefficient (EN 12667)	0,034 W/mk @ 0° - 0,039 W/mk @ 40° C
Vapour permeability (UNI EN 13469)	μ > 5000
Fire reaction class (EN 13501)	BL - s1, d0
Toxicity	null

## ITEMS

CODE	DESCRIPTION
SCD600015	"GREY LINE" - 1/4" INSULATED COPPER PIPE, COPPER THICKNESS 0,8mm, (roll 20 meter)
SCD600016	"GREY LINE" - 3/8" INSULATED COPPER PIPE, COPPER THICKNESS 0,8mm, (roll 20 meter)
SCD600017	"GREY LINE" - 1/2" INSULATED COPPER PIPE, COPPER THICKNESS 0,8mm, (roll 20 meter)
SCD600018	"GREY LINE" - 5/8" INSULATED COPPER PIPE, COPPER THICKNESS 0,8mm, (roll 20 meter)
SCD600019	"GREY LINE" - 3/4" INSULATED COPPER PIPE, COPPER THICKNESS 1,00 mm, (roll 20 meter)

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.