

Extensible gas hose for boiler connection coated in yellow polyolefin M / F

- cod. 25000120 - cod. 25000130 - cod. 25000140
- cod. 25000150 - cod. 25000160 - cod. 25000170
- cod. 25000180 - cod. 25000190 - cod. 25000200
- cod. 25000210 - cod. 25000220 - cod. 25000230
- cod. 25000240 - cod. 25000250 - cod. 25000260
- cod. 25000270



TECHNICAL SPECIFICATIONS:

- Max operating temperature +100°C
- AISI 316L stainless steel hose
- Stainless steel AISI 303 thread
- With yellow self-shrinking polyolefin protective sheath
- Inlet pressure max 0.5 bar

ITEMS

CODE	DESCRIPTION
25000120	COVERED EXTENDABLE HOSE Ø12 , L.80-120 MM, F1/2" M1/2"
25000130	COVERED EXTENDABLE HOSE Ø12 , L.120-200 MM, F1/2" M1/2"
25000140	COVERED EXTENDABLE HOSE Ø12 , L.220-400 MM, F1/2" M1/2"
25000150	COVERED EXTENDABLE HOSE Ø12 , L.280-520 MM, F1/2" M1/2"
25000160	COVERED EXTENDABLE HOSE Ø12 , L.80-120 MM, F3/4" M1/2"
25000170	COVERED EXTENDABLE HOSE Ø12 , L.120-200 MM, F3/4" M1/2"
25000180	COVERED EXTENDABLE HOSE Ø12 , L.220-400 MM, F3/4" M1/2"
25000190	COVERED EXTENDABLE HOSE Ø12 , L.280-520 MM, F3/4" M1/2"
25000200	COVERED EXTENDABLE HOSE Ø20 , L.80-120 MM, F3/4" M3/4"
25000210	COVERED EXTENDABLE HOSE Ø20 , L.120-200 MM, F3/4" M3/4"
25000220	COVERED EXTENDABLE HOSE Ø20 , L.220-400 MM, F3/4" M3/4"
25000230	COVERED EXTENDABLE HOSE Ø20 , L.280-520 MM, F3/4" M3/4"
25000240	COVERED EXTENDABLE HOSE Ø25 , L.80-120 MM, F1" M1"
25000250	COVERED EXTENDABLE HOSE Ø25 , L.120-200 MM, F1" M1"
25000260	COVERED EXTENDABLE HOSE Ø25 , L.220-400 MM, F1" M1"
25000270	COVERED EXTENDABLE HOSE Ø25 , L.280-520 MM, F1" M1"

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.