

# SBR - QUADRO

SBR - insulation and vibration-damping mat PANEL in vulcanised rubber

- cod. 11105073 - cod. SCC500001 - cod. SCC500002  
- cod. SCC500003



## TECHNICAL SPECIFICATIONS:

- Made of anti-UVA vulcanised SBR and EPDM natural rubber
- Acoustic and vibration-damping mat
- Density: 800 kg/m<sup>3</sup> (thickness 10 mm) 700 kg/m<sup>3</sup> (thickness 20 mm)
- Average surface hardness: 50 shore
- Maximum load: 5000 Kg/m<sup>3</sup>
- Fire resistance according to UNI EN 13501-1: F

Colour: Black

## DIMENSIONS

CODE	DIMENSIONS [mm]	THICKNESS [mm]
11105073	500 x 500	20
SCC500001	500 x 500	10
SCC500002	330 x 330	20
SCC500003	330 x 330	10

## ITEMS

CODE	DESCRIPTION
11105073	INSULATING MAT "SBR" VULCANIZED RUBBER VIBRATION DAMPER 500x500x20
SCC500001	INSULATING MAT "SBR" VULCANIZED RUBBER VIBRATION DAMPER 500x500x10
SCC500002	INSULATING MAT "SBR" VULCANIZED RUBBER VIBRATION DAMPER 330X330X20
SCC500003	INSULATING MAT "SBR" VULCANIZED RUBBER VIBRATION DAMPER 330X330X10

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.