

Radio frequency window contact for PROAIR system (also prepared for wiring)

- cod. GAD400254



DESCRIPTION

The window contact module ensures energy saving.

When doors and windows are opened, the window contact (transmitter) automatically signals to the "Polaris" control unit the closure of the area dampers, vents, fan coils or solenoid valves for floor systems to which the contact is associated.

The absence of wiring allows quick installation, the RF transmitter communicates with the control unit via radio frequency the possible opening of a window.

For more complex applications, the window contact can be wired to ensure its functionality at all times.

In addition, the window contact (RF transmitter), if configured, can assume the No Badge function and still allow the damper to be closed.

TECHNICAL SPECIFICATIONS:

- Power supply CR2032 battery (supplied as standard)
- RF transmission with "Polaris" control unit
- RF module and magnet
- RF module provided with terminal for management of a wired window contact
- Red window open LED
- Can be configured by the "Polaris" control units for Badge Management
- RF transmitter module dimensions 95 x 29 x 20 mm
- Dimensions of magnet 38 x 19 x 13 mm

FUNCTIONS

Opening the contact involves:

- Closure of the damper and/or opening of the zone solenoid valves
- Indication on the display of the chronothermostat

DATASHEET

- Display in Proair Multizone application
- Fastening by means of double-sided adhesive supplied

ITEMS

CODE	DESCRIPTION
GAD400254	WINDOW CONTACT FOR PROAIR SYSTEM

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.