

BBR

two-stage vacuum pump with rechargeable battery and vacuum gauge in carrying case

- cod. TSC100022 - cod. RIC00344



DESCRIPTION

Professional type pumps equipped with transport handle, ON / OFF switch, removable rechargeable lithium battery.

TECHNICAL SPECIFICATIONS:

- Two-stage pump
- Vacuum rating $2 \times 10^{-1} \mu$
- Lithium batteries: 18V - 5.0 Ah
- 1/4" SAE pump coupling
- Oil bath vacuum gauge $\varnothing 50$ mm
- Refrigerants: CFC, HCF, HFC (R12, R22, R32, R410a, R134a, 1234YF)
- Supplied in carrying case

THE CARRYING CASE CONTAINS:

- 1 Battery Charger
- 1 replacement lithium
- 1 bottle of oil
- 1 instruction booklet

TECHNICAL DATA

MODEL	FLOW RATE [l/min]	DEGREE OF VACUUM [micron]	POWER	FLEXIBLE HOSE COUPLER	OIL TANK CAPACITY [ml]	WEIGHT [kg]
TS56 BBR	56 l/min	1,5 micron	1/4 HP	1/4"	250 ml	3,3 kg

ITEMS

CODE	DESCRIPTION
TSC100022	TWO STAGE VACUUM PUMP TS56 BBR FOR R32 GAS
RIC00344	

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.