

30 m coiled PVC condensate drain pipe for duct installation

- cod. 11126326 - cod. 111263268 - cod. 11126327
 - cod. SCC300006 - cod. 111263274



TECHNICAL SPECIFICATIONS:

- Inner diameter: tolerance $\varnothing 18 - 0.5$ mm
- Plastic-coated rigid PVC-based material
- Flexibility: passes the test of no. 3000 flexions at $180^\circ + 5^\circ\text{C}$ and $+ 60^\circ\text{C}$.
- Bending radius: two times the diameter
- Crush resistance: class 2 greater than 220 Newton over 5 cm at $+ 23 \pm 2^\circ\text{C}$
- Impact resistance: class 3 2 kg from 10 cm at -5°C .
- Minimum temperature: class 1 $+ 5^\circ\text{C}$ -- Maximum temperature class 1 $+ 60^\circ\text{C}$.
- Electrical insulation resistance: greater than 100 megohms for 500 V operation for 1 min
- Fire resistance: passes "Glow wire test" at 850°C according to standard IEC EN 60695-2-11

DIMENSIONS

CODE	\varnothing [mm]	ROLL [m]
11126326	16	30
111263268	18	30
11126327	20	30
SCC300006	25	30
111263274	32	30

ITEMS

CODE	DESCRIPTION
11126326	CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 16 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT)
111263268	CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 18 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT)
11126327	CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 20 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT)
SCC300006	CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 25 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT)
111263274	CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 32 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT)

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.