

Washing liquid tank for 5 l systems

- cod. 11132210



DESCRIPTION

Flammable liquid for the internal washing of the systems, particularly suitable for cleaning in case of compressor replacement.

Evaporates very quickly.

It thoroughly removes all oil residues, rust, deposits and moisture inside the system. Totally compatible with rubber and metal components.

TECHNICAL SPECIFICATIONS:

- Appearance: colourless liquid
- Relative density [g/m^3]: 0.72- 0.85 kg/l (± 0.04)
- Flammability $< +21^\circ\text{C}$
- Boiling temperature: $+90^\circ\text{C}$ (± 5)
- Hydrosolubility: insoluble
- Available in 5 L formats

USES

This liquid solvent is specifically used in the internal piping of the car air conditioning system and refrigeration systems.

The flushing of air conditioning systems is one of the most important tasks in the event of repair or damage to the compressor. Flushing removes impurities and harmful substances from the air conditioning circuit.

It is necessary to carry out repairs in a workmanlike manner and to avoid costly subsequent repairs. This also protects warranty rights to suppliers and ensures customer satisfaction.

However, it is not possible to flush compressors, expansion/orifice valves, dryer filters or accumulators, they will therefore have to be bypassed with adaptors during the flushing cycle.

The valves and filters must be replaced at the end of the cleaning cycle.

WARNINGS

Use only with pneumatic equipment.

Do not flush compressors, expansion/orifice valves, dryer filters or accumulators.

SAFETY INFORMATION

Read and observe the safety warnings on the container's label.

For information regarding handling, transportation, etc., refer to the Safety Data Sheet (SDS) for the product in question.

ITEMS

CODE	DESCRIPTION
11132210	5 LITRE CAN OF SYSTEM CLEANING FLUID

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.