

Thermal flexible ducted flexible hose - double-walled aluminium phonic with internal antibacterial treatment

- cod. 11157085 - cod. 11157102 - cod. 11157127
- cod. 11157152 - cod. 11157160 - cod. PWC400018
- cod. 11157180 - cod. 11157203 - cod. 11157254
- cod. 11157305 - cod. 11157356 - cod. 11157457



TECHNICAL SPECIFICATIONS:

- Aluminium in grey colour
- Length 10 m
- Ø from 85 to 457 mm
- Bending radius 1 times the diameter
- Operating temperature: -30°C to +140°C
- Antibacterial treatment on the inner surface
- Conforms to EN 13180
- Reaction to fire NF P92-507:2004 M1
- Tested in accordance with ISO 22196:2007 for bacteria:
 - MRSA
 - E. coli
 - Salmonella Typhimurium
 - Staphylococcus Aureus

STRUCTURE

- Internal duct in rolled aluminium

- Insulation fibre mat in fiberglass th. 25 mm and density 16 kg/sqm
- Outer cladding “vapor-barrier” made from reinforced rolled aluminium
- Antimicrobial treatment using silver ions (AGT)

APPLICATIONS

- Air conditioning
- Thermal-ventilation

DIMENSIONS

CODE	INTERNAL Ø [mm]
11157085	85
11157102	102
11157127	127
11157152	152
11157160	160
PWC400018	165
11157180	180
11157203	203
11157254	254
11157305	305
11157356	356
11157457	457

DISTRIBUTED LOAD LOSSES FOR FULLY EXTENDED FLEXIBLE THERMAL- PHONIC DUCTING

ACOUSTIC ATTENUATION FOR DUCTED FLEXIBLE THERMAL HOSE - PHONIC HOSE IN DOUBLE-WALLED ALUMINIUM

1m	[Hz]					
Ø	125	250	500	1000	2000	4000
100	15	21	25	34	29	31
125	13	21	24	26	26	31
160	8	12	29	28	27	31
200	6	13	23	22	27	23
250	10	17	19	19	21	14
315	16	18	17	19	16	10
406	9	17	15	20	10	5

2m	[Hz]					
Ø	125	250	500	1000	2000	4000
100	17	22	25	43	48	31
125	13	21	26	34	37	32
160	15	17	27	35	44	36
200	11	21	26	39	29	34
250	7	17	24	27	27	23
315	13	21	20	22	24	16
406	14	16	16	22	16	8

3m	[Hz]					
Ø	125	250	500	1000	2000	4000
100	17	28	39	43	48	32
125	18	27	38	41	44	33
160	17	25	37	39	37	37
200	21	23	35	38	36	39
250	10	20	30	32	28	32
315	18	21	25	30	28	23
406	18	17	18	22	20	13

ITEMS

CODE	DESCRIPTION
11157085	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 85
11157102	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 102
11157127	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 127
11157152	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 152
11157160	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 160
PWC400018	THERMAL-FLEXIBLE THERMAL-PHONIC ALUMINIUM DOUBLE-PARTIC FLEXIBLE HOSE WITH INTERNAL ANTIBACTERIAL TREATMENT Ø165 mm L.10 m
11157180	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 180
11157203	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 203
11157254	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 254
11157305	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 305
11157356	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 356
11157457	INSULATED FLEXIBLE PIPE IN ALUMINIUM WITH INTERNAL ANTIBACTERIAL TREATMENT Ø 457

All rights relating to this publication are the exclusive property of Tecnosystemi SpA. Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.