

GREY LINE

single insulated copper pipe 50 m

- cod. SCD600010 - cod. SCD600011 - cod. SCD600012
- cod. SCD600013 - cod. SCD600014



DESCRIPTION

Copper pipe Cu-DHP (in accordance with EN 12735-1) covered with a closed-cell polyethylene foam sheath with a robust grey tear-resistant outer film.

DOES NOT CONTAIN FREON (HCFCs, CFCs or HFCs) in accordance with Law No. 549 of 28/12/1993.

TECHNICAL DATA

CODE	Ø [inch]	Ø [mm]	COPPER THICKNESS [mm]	SHEATH THICKNESS [mm]	MAX. OPERATING PRESSURE [bar]	BURST PRESSURE [bar]
SCD600010	CU 1/4"	6.35	0.8	6	107.9	515.9
SCD600011	CU 3/8"	9.52	0.8	6	71	339.4
SCD600012	CU 1/2"	12.7	0.8	6	53.9	258
SCD600013	CU 5/8"	15.88	1	10	50.8	243.1
SCD600014	CU 3/4"	19.05	1	10	42.4	202.6

TECHNICAL SPECIFICATIONS OF THE SHEATH

SPECIFICATIONS	TECHNICAL DATA
Operating temperature	-45° C +105° C
Density	30 kg / m ³
Technical conductivity coefficient (EN 12667)	0,034 W/mk @ 0° - 0,039 W/mk @ 40° C
Vapour permeability (UNI EN 13469)	μ > 5000
Fire reaction class (EN 13501)	BL - s1, d0
Toxicity	null

ITEMS

CODE	DESCRIPTION
SCD600010	"GREY LINE" - 1/4" INSULATED COPPER PIPE- COPPER THICKNESS 0,8 mm - (roll 50 meter)
SCD600011	"GREY LINE" - 3/8" INSULATED COPPER PIPE- COPPER THICKNESS 0,8 mm - (roll 50 meter)
SCD600012	"GREY LINE" - 1/2" INSULATED COPPER PIPE- COPPER THICKNESS 0,8 mm - (roll 50 meter)
SCD600013	"GREY LINE" - 5/8" INSULATED COPPER PIPE- COPPER THICKNESS 1,0 mm - (roll 50 meter)
SCD600014	"GREY LINE" - 3/4" INSULATED COPPER PIPE- COPPER THICKNESS 1,0 mm, (roll 25 meter)

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.
 Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

