

PA-PLUS

digital current clamp

- cod. 11131113 - cod. TSD500007



TECHNICAL SPECIFICATIONS:

- Backlit LCD display, max display value 4000
- Maximum measurable current 400 A
- Maximum conductor cross-section 30 mm (11.8")
- Range: Aca/Ua, Dca/Ua, ACV, DCV, Ohm, continuity, capacity and temperature
- Continuity buzzer (<40 ohm)
- Alternating current 0.1- 4000 Ua/0.01 A - 400 A \pm (2.0% +10)
- Direct current 0.1- 4000 Ua \pm (1.0% +2)
- Alternating voltage 1 mv-600 V \pm (1.0% +3)
- Continuous voltage 1m v-600 V \pm (0.8% +2)
- Temperature (K) -50° C - 1200° C e 158° F - 1999° F
- Low battery indication
- Auto shut-down (30 minutes)
- R-H range block
- Select: selection button for Aca/Ua, Dca/Ua, Acv/Dcv and Ohm/Continuity composite functions.
- Overload display
- Automatic range
- D-h data block
- Weight 280 g
- Power supply battery 2 x 1.5 V type supplied
- Dimensions W 205 x H 39 x D 64 mm

ITEMS

CODE	DESCRIPTION
11131113	DIGITAL CURRENT CLAMP "PA PLUS"
TSD500007	DIGITAL CLAMP METER "PA-PLUS" - WITH CALIBRATION REPORT

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.